


# DATASHEET Ci2



## FEATURES

2½" low-mid driver  
 ¾" silk dome tweeter  
 Triangular ABS cabinet  
 IP64 rated  
 Mounts without brackets  
 Hidden cable connection

## COLOURS



## Description


Ci2 is an ultra compact 2-way full-range speaker with a full-bodied sound. Featuring a tweeter with highly uniform dispersion, coverage is very wide and as such the speaker does not need to be angled, but will cover the entire room with sound while placed in the corner. The waveguide of the tweeter contributes to the very controlled dispersion and increases sensitivity. The cabinet design is exceptionally discreet while offering natural, clean sound.

With the patented triangular design, installation is fast and easy. The integrated mounting points allows the cabinet to mount flush in corners or onto walls and ceilings without brackets. Two cabinets can be mounted together to increase coverage to 180 degrees. The cable terminal is hidden behind the grille with the cable mounted from the rear of the cabinet, making cables invisible both in vertical and horizontal applications.

Ci2 plays well beyond its size and is very well suited for background sound in coffee shops, hotels and retail outlets.

For enhanced bass performance, the Ci2 can be teamed indoors with our C8S and C12S subwoofers.

## DATA



Sensitivity SPL / 1W @ 1m:	84 dB
Maximum SPL, Long Term:	99 dB
Maximum SPL, Peak:	105 dB
Frequency response:	140-20.000 Hz
Nominal impedance:	8 Ω
Dispersion:	100° vertical / 100° horizontal
Ingress Protection:	IP64
Recommended amplifier:	15-30 W
Measurements:	181 x 135 x 102 mm (7.13 x 5.32 x 4.02 in)
Weight:	0.75 kg (1.65 lb)
Colour:	White (RAL9010) Black (RAL9005)

# DATASHEET Ci2

## Architectural Specifications

The loudspeaker system shall consist of a 2 ½" woofer and a ¾" tweeter coupled to a waveguide with an even dispersion of nominal 100 by 100 degree.


Specifications of a typical production shall be as follows: Sensitivity SPL / 1W @ 1m shall be at least 84 dB. Nominal impedance shall be 8 ohm, with minimum impedance being 8 ohm @15 kHz. Recommended amplifier shall be 15-30 W. Frequency response shall be from 140-20kHz +/- 3 dB.

The enclosure shall be triangular in shape with no visible cable terminals and with a 90 degree angle allowing the speaker to be mounted flush in corners or onto wall and ceiling without brackets using the integrated mounting points. It shall be manufactured of ABS plastic shall have IP64 outdoor rating. For theft deterrence, the installation points shall be hidden behind the grille. Speaker cable terminals shall be push terminals placed on the front baffle.

Cabinet finish shall be white or black. Outside dimensions shall be no greater than 181 mm (height) x 135 mm (width) x 102 mm (depth) and weight shall be 0,75 kg.

The loudspeaker system shall be the Ci2 by Blaze Audio

## FREQUENCY RESPONSE



## IMPEDANCE

