

CONNECT • CONFIGURE • CONTROL

BLAZE



TABLE OF CONTENT

PowerZone[™]
Connect 2U

PowerZone[™] Connect 1U

12 Wall-S1

PowerZone™ Control

22 PowerZone™

26 Loudspeakers

Blaze Audio specialize in pro audio solutions tailored for the installed sound market.


Our products deliver the power and exceptional sound performance demanded in commercial locations, and the technology, quality, and reliability expected by the professional audio market.

blaze-audio.com

BLAZE

MORE POWER STILL CONNECTED

The PowerZone™ Connect 2U amplifiers stand as robust, full rack DSP amplifiers, providing adaptable and reliable power output across 2, 4, and 8 channel variations, offering a total system power range from 1000 W to 6000 W.



PowerZone™ **Connect 2U**



1002 1000 W | 2 CH



1502 1500 W | 2 CH



2004/2004D

2000 W | 4 CH



3004/3004D

3000 W | 4 CH



4008 4000 W | 8 CH




6008 6000 W | 8 CH



PowerZone™ Connect series 2U

The PowerZoneTM Connect 2U series is a line of ultra-reliable, full-matrix DSP-enabled Class-D amplifiers that delivers exceptional system configuration and flexible output, with a total system power ranging from 1000 W to 6000 W. The PowerZoneTM Connect 2U series powers both conventional low-impedance (2 Ω to 16 Ω) loudspeakers and constant voltage (70 V/100 V) transformer-coupled loudspeakers, and features proportional distribution in both Lo-Z and Hi-Z modes. Specific models of the PowerZoneTM Connect 2U amplifiers offer compatibility with Audinate DanteTM AoIP networks and installations.

Our intuitive PowerZone™ Control web app is built into all our PowerZone™ Connect amplifiers for easy system setup. PowerZone™ Control facilitates effortless customization of even the most challenging audio/voice systems by delivering many DSP configuration options and tuning features, including multizone setup, input mixing, priority and ducking, restriction, input and output EQ, S/PDIF output routing, high-pass filter, speaker presets, delay, Wall-S1 controller configuration, Sine generator, and much more.



TECHNICAL OVERVIEW



- 1. RJ45 connection Direct Network access (Ethernet)
- 2. Dante[™] AoIP RJ45 port
- **3. GPIO Connections** External control & monitoring
- 4. Wi-Fi antenna
- 5. S/PDIF digital input/output

- 6. 4 x Unbalanced RCA input
- 7. 4 x Balanced inputs
- 8. 4 x Lo-Z outputs or 2 x Hi-Z outputs
- 9. Mains Power IEC 90-268 Vac input

KEY FEATURES

- Full rack form factor
- Full-matrix DSP configuration via PowerZone™ Control web app (built-in)
- Hybrid power distribution in both Lo-Z and Hi-Z
- Powered by Pascal UMAC[™] Class-D technology

- Audinate Dante[™] AoIP compatibility (optional)
- S/PDIF digital input/output
- Configurable GPIO
- ErP and Energy Star compliant
- UL listed audio equipment

Blaze Audio | hello@blaze-audio.com

6/36

Blaze_Products_2023_full_Dec2023_36-pages.indd 6



MODEL OVERVIEW

full datasheet









| Model | PowerZone™ Connect 1002 | PowerZone™ Connect 1502 | PowerZone™ Connect 2004/2004D | PowerZone™ Connect 3004/3004D |
|----------------------|------------------------------------|------------------------------------|------------------------------------|------------------------------------|
| Channels | 2 x Lo-Z/1 x Hi-Z | 2 x Lo-Z/1 x Hi-Z | 4 x Lo-Z/2 x Hi-Z | 4 x Lo-Z/2 x Hi-Z |
| Output Power @ 2 Ω | 2 x 500 W (SE) | 2 x 750 W (SE) | 4 x 500 W (SE) | 4 x 750 W (SE) |
| Output Power @ 4 Ω | 2 x 500 W (SE) 1 x 1000 W (BTL) | 2 x 750 W (SE) 1 x 1500 W (BTL) | 4 x 500 W (SE) 2 x 1000 W (BTL) | 4 x 750 W (SE) 2 x 1500 W (BTL) |
| Output Power @ 8 Ω | 2 x 250 W (SE) 1 x 1000 W (BTL) | 2 x 400 W (SE) 1 x 1500 W (BTL) | 4 x 250 W (SE) 2 x 1000 W (BTL) | 4 x 400 W (SE) 2 x 1500 W (BTL) |
| Output Power @ 70 V | 1 x 1000 W (BTL) | 1 x 1200 W (BTL) | 2 x 1000 W (BTL) | 2 x 1200 W (BTL) |
| Output Power @ 100 V | 1 x 1000 W (BTL) | 1 x 1500 W (BTL) | 2 x 1000 W (BTL) | 2 x 1500 W (BTL) |
| Total System Power | 1000 W | 1500 W | 2000 W | 3000 W |






| Model | PowerZone™ Connect 4008 | PowerZone™ Connect 6008 |
|----------------------|------------------------------------|------------------------------------|
| Channels | 8 x Lo-Z/4 x Hi-Z | 8 x Lo-Z/4 x Hi-Z |
| Output Power @ 2 Ω | 8 x 500 W (SE) | 8 x 750 W (SE) |
| Output Power @ 4 Ω | 8 x 500 W (SE) 4 x 1000 W (BTL) | 8 x 750 W (SE) 4 x 1500 W (BTL) |
| Output Power @ 8 Ω | 8 x 250 W (SE) 4 x 1000 W (BTL) | 8 x 400 W (SE) 4 x 1500 W (BTL) |
| Output Power @ 70 V | 4 x 1000 W (BTL) | 4 x 1200 W (BTL) |
| Output Power @ 100 V | 4 x 1000 W (BTL) | 4 x 1500 W (BTL) |
| Total System Power | 4000 W | 6000 W |

BLAZE

ALL SET-UP FROM YOUR PHONE

The PowerZone™ Connect 1U series is a line of DSP-enabled Class-D amplifiers designed to make system installers' lives easier, offering unparalleled reliability and efficiency, along with exceptional system configuration. The compact form factor, makes them an ideal choice for audio/voice installation projects with limited space constraints that demand high-output performance.



PowerZone™ **Connect 1U**

△Dante









122/122D 125 W | 2 CH

252 250 W | 2 CH

250 W | 4 CH

504/504D

500 W | 4 CH







508

500 W | 8 CH

1008

254

1000 W | 8 CH



PowerZone™ Connect series 1U

The PowerZone[™] Connect 1U series is a line of DSP-enabled Class-D amplifiers designed to simplify the lives of system installers, providing unmatched reliability, efficiency, and exceptional system configuration. Their compact form factor makes them an ideal choice for audio/voice installation projects with limited space constraints, demanding highoutput performance of up to 1000 W. The 1U family powers both conventional low-impedance (4Ω to 16Ω) loudspeakers and constant voltage (70 V/100 V) transformer-coupled loudspeakers, and features automatic power-sharing technology for proportional distribution in both Lo-Z and Hi-Z modes.

Specific models of the PowerZone™ Connect 1U amplifiers offer compatibility with Audinate Dante™ AoIP networks and installations.

Our intuitive PowerZone™ Control web app is built into all our PowerZone™ Connect amplifiers for easy system setup. PowerZone™ Control facilitates effortless customization of even the most challenging audio/voice systems by delivering many DSP configuration options and tuning features, including multizone setup, input mixing, priority and ducking, restriction, input and output EQ, S/PDIF output routing, high-pass filter, speaker presets, delay, Wall-S1 controller configuration, Sine generator, and much more.

KEY FEATURES

- Compact form factor
- Full-matrix DSP configuration via PowerZone™
 Control web app (built-in)
- Hybrid power distribution in both Lo-Z and Hi-Z
- Powered by Pascal UMAC[™] Class-D technology
- Flexible power sharing across output channels

- Audinate Dante[™] AoIP compatibility (optional)
- S/PDIF digital input/output
- Configurable GPIO
- ErP and Energy Star compliant
- UL listed audio equipment







- 1. RJ45 connection Direct Network access (Ethernet)
- 2. Dante[™] AoIP RJ45 port
- 3. **GPIO Connections** External control & monitoring
- 4. Wi-Fi antenna
- 5. S/PDIF digital input/output

- 6. 4 x Unbalanced RCA input
- 7. Balanced inputs
- 8. 4 x Lo-Z outputs or 2 x Hi-Z outputs
- 9. Mains Power IEC 90-268 Vac input

Blaze Audio | hello@blaze-audio.com



Use QR to acces full datasheet



MODEL OVERVIEW












| Model | PowerZone™ Connect 122/122D | PowerZone™ Connect 252 | PowerZone™ Connect 254 | PowerZone™ Connect 504/504D |
|---|---|---|--|--|
| Channels | 2 x Lo-Z/1 x Hi-Z | 2 x Lo-Z/1 x Hi-Z | 4 x Lo-Z/2 x Hi-Z | 4 x Lo-Z/2 x Hi-Z |
| Output Power @ 4/8 Ω | 2 x 60 W | 2 x 125 W | 4 x 60 W | 4 x 125 W |
| Output Power @ 70/100 V | 1 x 125 W | 1 x 250 W | 2 x 125 W | 2 x 250 W |
| Powershare (up to) Across all channels | 1 x 125 W | 1 x 250 W | 1 x 250 W | 2 x 250 W |
| Power Consumption | 75 W | 75 W | 75 W | 150 W |
| Dimensions | 44 x 220 x 213 mm (1.7 x 8.7 x 8.4 in) | 44 x 220 x 213 mm (1.7 x 8.7 x 8.4 in) | 44 x 220 x 319 mm (1.7 x 8.7 x 12.6 in) | 44 x 220 x 319 mm (1.7 x 8.7 x 12.6 in) |
| Total System Power | 125 W | 250 W | 250 W | 500 W |






| Model | PowerZone™ Connect 508 | PowerZone™ Connect 1008 |
|--|---|---|
| Channels | 8 x Lo-Z/4 x Hi-Z | 8 x Lo-Z/4 x Hi-Z |
| Output Power @ 4/8 Ω | 8 x 60 W | 8 x 125 W |
| Output Power @ 70/100 V | 4 x 125 W | 4 x 250 W |
| Powershare (up to) Across all channels | 2 x 250 W | 4 x 250 W |
| Power Consumption | 150 W | 300 W |
| Dimensions | 44 x 440 x 319 mm (1.7 x 17.3 x 12.6 in) | 44 x 440 x 319 mm (1.7 x 17.3 x 12.6 in) |
| Total System Power | 500 W | 1000 W |

BLAZE

















Wall-S1 controller

The Wall-S1 is a wall mounted networked/ PoE controller for remote control of any Blaze Audio PowerZone™ Connect amplifier. It enables end-user control of input source and volume, as well as many advanced features and settings that system installers can configure and customise to meet the needs of a specific location. It is simple to set up, configure, and customize any installed system, and any sound zone.

With the ability to pair up to $8 \times \text{Wall-S1}$ controllers per PowerZoneTM Connect amplifier and assign them to any configured audio zones, installers can effortlessly set up projects using this straightforward networked controller. Real-time syncing within the same zone, PIN code protection for system security & access, and customizable color screens are among the advanced features that can be personalized to ensure the perfect fit for each location.



KEY FEATURES

- Danish-designed, high-performance polymer material with a touch-friendly matte finish and concealed screws
- Available in EU and US versions, standard white RAL9003 and black RAL9005
- 4 color screen schemes, 4 brightness and 4 button backlight options
- Instant network pairing and configuration for up to 8 Wall-S1 controllers with each
- PowerZone[™] Connect amplifier
- Optional 4-digit PIN code protection
- Works with PowerZone™ Connect amplifiers

Blaze Audio | hello@blaze-audio.com

(

TECHNICAL OVERVIEW









2. Control Button Push, Hold, Rotate



- 3. **Mounting holes** Fits standard electrical boxes
- 4. **PoE Connection** Connection and power in-one















| Model | W-EU | B-EU | W-US | B-US |
|----------------------------------|--|--------------------|-------------------------------------|--------------------|
| Amplifier Compatibility | Blaze Audio - PowerZone™ Connect series | | | |
| Colour | White (RAL9003) | Black (RAL9005) | White (RAL9003) | Black (RAL9005) |
| External Dimensions (H x W) | 86.79 x 86.79 mm (3.42 x 3.42 in) | | 115.1 x 70.6 mm (4.53 x 2.78 in) | |
| Weight | 120 g (4.2 oz.) | | 120 g (4.2 oz.) | |
| Maximum Cable Length (CAT 5e) | 100 m (328 ft) | | | |
| Power Consumption | PoE Class 1 / 3.84 W max | | | |
| Power Supply | Power to the RJ45 ethernet port on the rear of device using a category 5e cable (or faster STP) with the use of a standard PoE switch, or PoE injector | | | |





Our web app, PowerZone™ Control, is the most versatile DSP controller available for configuring audio/voice systems in locations requiring multizone audio set up with multiple mic talk overs.







PowerZone™ Control

Pc/Mac
ANY BROWSER

Tablet
ANY BROWSER

Mobile
ANY BROWSER




PowerZone™ Control

Our web app, PowerZone™ Control, is the most versatile DSP controller available for configuring audio/voice systems in locations requiring multi-zone audio set up with multiple mic talk overs. PowerZone™ Control facilitates effortless customization of even the most detailed audio/voice systems and adept management of multiple DSP configurations and tuning features, such as multi-zone setup, input mixing, priority and ducking, restriction, input and output EQ, S/PDIF output routing, highpass filter, speaker management and presets, delay, Wall-S1 controller configuration, Sine generator, and much more.

PowerZone™ Control caters to the demanding requirements of advanced system installs in locations such as retail stores, restaurants, hotels, educational facilities, theatres, bars, cafes, fitness & sports venues, vast hospitality spaces, and spaces with multiple meeting/conference rooms.

PowerZone[™] Control is embedded in our PowerZone[™] Connect DSP amplifiers, and can be accessed from any device and browser via the PowerZone[™] Connect built-in Wi-Fi or RJ45 network port.



KEY FEATURES


- Multi-Zone setup: Configure a complex multi-zone system with advanced settings and zone management
- Input mixing: Combine input sources into a total of 8 separate mixers
- Priority and ducking: Configure priority input and ducking to override primary audio in zones
- Input and output EQ: Virtual parametric EQ on each analog input and all outputs.
- S/PDIF output routing; Route zones and inputs to S/PDIF and expand the install with another amplifier

- High-pass filter for better mic speech clarity & natural sound
- Speaker presets: Apply speaker presets for brands like Bose, Yamaha, JBL, Sonance and more, or create your own
- Delay: Up to 100.00 ms of delay to any output (112.50 ft/34.3 m)
- In room controller configuration: Configure Blaze Audio Wall-S1 controllers and 3rd party controller brands like Crestron, Control4, and Q-Sys

20/36 Blaze Audio | hello@blaze-audio.com


TECHNICAL OVERVIEW











- 1. Multi-Zone setup
- 2. Input mixing

- 3. Input & output EQ
- 4. External Devices Wall-S1 controllers

BLAZE

FLEXIBLE, RELIABLE POWER

The PowerZone™ series of installation power amplifiers is designed to provide reliable and adaptable high-quality audio power.





PowerZone™

BLAZE PARTITION

252

250 W | 2 CH



504

500 W | 4 CH



1004

1000 W | 4 CH



PowerZone™ series

The PowerZone™ series of install power amplifiers are designed to provide versatile and reliable high-performance audio power. Each output channel can be independently configured to drive either Lo-Z or Hi-Z loads – making it so much more flexible and versatile than other full rack products. This means a system can be easily configured with any power output, and drive both Lo-Z and Hi-Z loudspeakers – from just one clever amplifier. Total available power is automatically shared across channel

pairs – thanks to our power sharing technology (252 and 504 models only). The ultra-compact PowerZone[™] can be installed in locations where other products cannot – and has desk and wall mount brackets as well as full rack supports.

PowerZone[™] is a robust and energy-efficient amplifier, that offers quick set-up and custom configuration options, and like all PowerZone[™] products, this reliable, high-performance amplifier has a 5-year warranty.



KEY FEATURES

- All channels deliver low & high impedance loads meaning one amplifier can replace two, and saves you costs and installation time
- Total power is automatically shared across the output channels use one PowerZone™ amp to utilize the power where you need it (model-specific feature)
- Ultra-compact form factor means the ½ rack PowerZones are so small and neat they can be installed in spaces where other brands cannot
- Consolidate products and brands save the hassle of sourcing multiple amplifiers when PowerZone™ can be used on many different install sites

- Easy to configure DIP Switches allow you to set up on-site as you need and has front panel control lock to stop unwanted changes to your setup
- GPIO interface enables adding of any standard remote control (potentiometer) to the system
- Class leading energy efficiency means a day-to-day energy saving and long-term low cost of ownership
- Pascal's UMAC™ Class-D amplifier technology with market proven, ultra-reliable U-PRO amp modules
- PowerZone[™] quality and reliability are backed up with a 5-year warranty

24/36 Blaze Audio | hello@blaze-audio.com



02/01/2024 09.52

(

TECHNICAL OVERVIEW

Use QR to acces full datasheet







- 2. Channel LED Signal status indicators
- 3. Channel Gain Adjust Controls One per channel
- **4. Maintenance Port** Only used by Blaze Audio
- **5. DIP Switches** See user manual for configuration options



- 6. **GPIO Connections** External control & monitoring
- 7. **INPUT** All channels
- **8. OUTPUT** All channels
- **9. Mains Power** IEC 90-268 Vac input













| Model | PowerZone™ 252 | PowerZone™ 504 | PowerZone™ 1004 |
|--|---|---|--|
| Channels | both channels Lo-Z and/or Hi-Z | all channels Lo-Z and/or Hi-Z | all channels Lo-Z and/or Hi-Z |
| Output Power @ 4/8 Ω | 2 x 125 W | 4 x 125 W | 4 x 250 W |
| Output Power @ 70/100 V | 2 x 125 W | 4 x 125 W | 4 x 250 W |
| Powershare (up to) Across all channels | 1 x 250 W | 2 x 250 W | N/A |
| Power Consumption | 75 W | 150 W | 300 W |
| Dimensions | 44.5 x 220 x 262 mm (1.75 x 8.66 x 10.31 in) | 44.5 x 220 x 337 mm (1.75 x 8.66 x 13.27 in) | 44.5 x 440 x 292 mm (1.75 x 17.32 x 11.50 in) |
| Total System Power | 250 W | 500 W | 1000 W |







Loudspeakers

Our two loudspeakers employ crossover points of 420 Hz and 520 Hz, seamlessly extending up to 18 KHz for a smoother, full-range frequency response across the entire reflective physical space, eliminating speech intelligibility gaps. Utilizing advanced testing methods (Circumstantial Predictability) and mathematical modeling, our unit design ensures optimal real-

world performance. Cutting-edge acoustic scanning technology, in a multi-axis 3D setting, analyzes directivity, sound power, and SPL. Professionally tuned for PowerZone™ Connect, digital processing & amplification using DSP, our speakers elevate your configuration, providing unparalleled listening experiences.





KEY FEATURES

- Highly focused pattern with consistent frequency response throughout the frequency range, on and off-axis.
- Symmetrical dispersion pattern.
- Custom 5" low-frequency drivers, with tightly designed acoustic centers.
- 2" vertically arrayed HF drivers.

- Super wide symmetrical horizontal pattern control
- Ultra low-distortion drivers.
- Powder coated steel grille with a high transmission ratio.
- Tuned with a passive crossover and integration with Blaze Audio amplifiers with custom DSP and FIR filtering.









MODEL OVERVIEW

| Model | CBL523 | CBL528 |
|---------------------------------------|---|--|
| Frequency Response (-3 dB) | 71 Hz - 18 kHz¹ | 54 Hz - 18 kHz ² |
| Frequency Range (-10 dB) | 55 Hz - 18 kHz | 48 Hz - 18 kHz ² |
| High-Pass Filter | 48 Hz (Recommended) | 48 Hz - w/ minimum 24 dB / Butterworth Filter |
| Horizontal Nominal Dispersion (-6 dB) | 160° | 180° |
| Vertical Nominal Dispersion (-6 dB) | 55° (Average beamwidth, 500 Hz - 5 kHz) | 45° |
| Recommended Crossover Frequency | 520 Hz | 420 Hz (acoustic, active, external DSP) |
| Long Term Power Handling | Full range: 160 W | Low Freq: 320 W (1280 W peak) ³ High Freq: 200 W (800 W peak) ³ |
| Impedance | 4 Ω | Low Freq: 8 Ω High Freq: 5.2 Ω |
| Net Weight | 6.8 kg/15 lbs | 17.46 kg/38.5 lbs |
| Dimensions (HxWxD) | 205.3 x 350 x 226.2 mm (8.08 x 13.78 x 8.90 in) | 494.3 x 494 x 406.16mm (19.46 x 19.45 x 15.99 in) |
| Color | Black or White | Black or White |
| Max SPL @ 1W/1m (2.83v) | 119 dB | 121 dB SPL (131 dB SPL peak) |

¹Frequency response and range measured on-axis in an anechoic environment.

³ Power handling tested using pink noise filtered to meet IEC 268-5, 6 dB crest factor, 100 hours, with recommended EQ.





Blaze Audio | hello@blaze-audio.com



² Frequency response and range measured on-axis with recommended active EQ in an anechoic environment.



CASE STUDY





Installation by: Ata Tech

EUROMAST ROTTERDAM

POWERED BY BLAZE AUDIO AMPLIFIERS

The lift cabin of the Euromast is equipped with a 360 degrees Spatial sound system. This sends the sound through 20 speakers and creates a virtual 3D surround sound effect. Each speaker is individually controlled and provides a unique audio experience that surrounds you, putting you right in the middle of the action. The entire show is timecode-controlled, so that the light, the soundtrack, the voice-over, and the movement of the lift all run at exactly the same time.

To get the immersive sound experience perfect, there was a need for a compact amplifier with perfect sound quality. With $5 \times PowerZone^{TM}$ Connect 254 used to drive the 2-way speakers, which give the sound directly to the visitor and $1 \times PowerZone^{TM}$ Connect 504 used to drive the $2 \times S$ sub speakers in the lift.

Blaze Audio | hello@blaze-audio.com



CASE STUDY

PYRMONT POINT HOTEL SYDNEY

POWERED BY BLAZE AUDIO AMPLIFIERS

Faced with the challenge of updating its sound system while preserving its distinctive character, Pyrmont Point Hotel, a heritage gem in Sydney's Pyrmont district, sought the expertise of Jands Pty Ltd, our Australian partner and leader in audio, video, and lighting solutions. The collaboration led to the selection of Blaze Audio's PowerZone Connect series for amplification across the hotel's various venues, encompassing 9 zones, including a larger event space hosting DJs and live bands, cocktail lounges, a balcony, and a bistro.

Nathan David, the owner of Pyrmont Point Hotel, expressed his delight with the upgrade: "The transformation of our sound system has been astounding. The integration of Blaze Audio amplifiers has been central to this improvement, offering our



guests a more sophisticated and immersive audio experience". Ilias Sintrikos, Business Development Manager - Hospitality at Jands, remarks, "Blaze Audio was the perfect fit for Pyrmont Point Hotel. Its amplifiers brought the clarity and richness needed to elevate the venue's audio experience".

Products installed:

- 2 x Powerzone Connect 3004
- 2 x Powerzone Connect 2004
- 1 x Powerzone Connect 254
- 1 x Powerzone Connect 252

Scan the QR code to watch the case study film provided by Jands.





Installation by: Jands Pty Ltd

Blaze Audio | hello@blaze-audio.com

Blaze_Products_2023_full_Dec2023_36-pages.indd 31 02/01/2024 09.52

SOLUTIONS



Retail Environments

Music plays a crucial role in the success of retail businesses as it affects customer mood, behavior, and purchase decisions. At Blaze Audio, we provide a variety of system designs featuring amplifier models ranging from 60 W to 750 W per channel, which are easy to configure. Our PowerZone™ Control web app allows you to restrict or set maximum and minimum volume levels across different retail zones. Additionally, our networked wall controllers help manage the source and volume, providing customization and PIN code protection for added security.





Restaurant and dining

Regardless of the size of the restaurant, music is an essential element of the overall dining experience. As different areas within a restaurant have varying audio requirements, a flexible audio system is necessary. For instance, busy bar areas may require higher sound pressure levels, while cosy dining areas may require much less. Our PowerZone[™] amplifiers provide the ideal solution, delivering the required power output and flexibility to provide sound to any zone or room, regardless of its size.



Blaze_Products_2023_full_Dec2023_36-pages.indd 32





Bars and Cafes

Our selection of amplifiers is designed to meet the sound pressure needs of any hospitality project, regardless of its size. With channel output available in both Lo-Z and Hi-Z, as well as smart power sharing and easy system setup, PowerZone™ amplifiers are an ideal choice for bars and cafes. By utilizing our PowerZone™ Control web app and networked controllers, any project can be swiftly configured to provide exceptional background sound in locations with multiple zones.





Hotels and Education sites

Our PowerZone™ Connect amplifier series and web app, PowerZone™ Control, provide effortless customization for full DSP configuration of audio/voice systems in locations requiring multi-zone setups with sound and multiple mic talk overs. This is particularly crucial in hotels, educational facilities, auditoriums, theaters, and vast hospitality spaces with multiple meeting rooms. Furthermore, our S/PDIF output routing feature facilitates zone and input routing allowing easy system expansion through multiple interconnected amplifiers.



•

SOLUTIONS



Fitness & Sports venues

Fitness projects demand high-quality sound systems with exceptional flexibility. Background music is played in gym and workout areas, while the same system is also required to provide full power with mic talk overs in classes such as spinning.

PowerZone™ amplifiers can handle these demanding environments, as automatic power sharing delivers the necessary power across any channel and loudspeaker setup while easy pre-set inputs for audio/voice mixes for different fitness activities can be configured using our PowerZone™ Control web app.





Corporate, Government & Enterprise

The Corporate, Government, and Enterprise sector has a wide range of applications for audio systems, with or without multiple mic talk overs, including conferences and boardrooms, meeting areas of any size, warehouses, cafeterias, and break areas.

Blaze Audio is an ideal choice for these applications, as our solutions are reliable, flexible, and easy to set up and use. Our PowerZone™ amplifiers are capable of covering different sound pressure needs, and up to 8 Wall-S1 controllers can be networked to cover many rooms or large spaces.







House of Worship

House of Worship projects require reliable, high-quality amplification of voice, often covering a large distribution area. Blaze Audio solutions are perfect for HoW projects, thanks to our high-quality amplification at low power and superior speech intelligibility. Our PowerZone™ Connect amplifiers offer a wide range of total system power, between 125 W and 3000 W, and can be set up with any speaker load. Moreover, our PowerZone™ Control web app simplifies audio setup, enabling multiple mic talk-overs, and making it a hassle-free process.





CONNECT • CONFIGURE • CONTROL

blaze-audio.com